Design and Development of a 100 MVA HTS Generator

Los Alamos National Laboratory

<u>Joe Waynert</u>, Steve Ashworth, Todd Jankowski, Coyne Prenger, Jim Stewart, Dean Peterson

Arsalan Razani, *University of New Mexico*

FY2004 Project Funding: \$430 k (LANL/DOE)

\$430 k (GE in-kind)

2004 DOE Annual Peer Review Washington, DC July 27-29, 2004





Outline

- Results of FY 2004
 - Long Term Vacuum Maintenance
 - Heat Pipe Cooling
 - Closed Loop, Passively Pumped Cooling
 - AC Loss/Over-current Fault
- FY 2004 Performance
- FY 2005 Plans
- Research Integration





Long Term Vacuum Maintenance


reduce heat loads | reduce refrigeration \$ | increase efficiency

- Outgassing properties of materials
 - gas species
 - quantity of each species
- Getter material identification and characterization (LANL ID'd, supplied, discussed; GE using vendor info)
- Vacuum maintenance prescription: linking outgassing and amount/type of gettering mat'l (LANL article published in Adv. Cryo. Eng., Vol 49)





Outgassing Measurements - 1




pump chamber

sample chamber





Outgassing Measurements - 2





Outgassing Measurements - 3

Status

- Over 100 outgassing experiments performed each requires 50 hours or more
- 12 different materials measured
- Determined uncertainty & repeatability
- Determined effect of orifice size
- Assessing low temperature bake-out of samples
- Assessing impact of 'non-virgin' samples
- Coordinating results with emissivity degradation






smaller △T load/cooler reduce refrigeration reduce smaller △T load/cooler reduce refrigeration

Ultimately transfer heat from load to cryocoolers

Higher performance alternative

to GE baseline

Orders-of-magnitude more efficient heat transfer than pure conduction





Axis of rotation


Heat pipe thermal model (unique high-g environment)

very detailed axi-symmetric

incorporates rotation induced body forces


 indicates vapor will return to condenser against g-forces

Cross-section view





Room-temperature apparatus to verify model and performance







- All components are at LANL being assembled
- Heat pipe is undergoing stationary bench tests (developing wick assembly procedures)










Closed Loop Passively Pumped Cooling


smaller ∆T load/cooler reduce refrigeration reduce smaller ∆T load/cooler reduce refrigeration reduce redu



rotation

GE Proposed LANL analyzed

Simple but requires rotation









AC Loss - Over-current Fault

protect HTS coil during fault condition thermal & voltage issues; impact on cooling; recovery time

fault current profile

Picture of apparatus









FY 2004 Performance - 1

LANL is responding to changes in CRADA scope:

Outgassing material characterization;

new materials being received; over 100 different measurements performed; two reports sent, third in process, (increased scope at GE request).

✓ Getter material evaluation;

GE/LANL discussions; vendor discussions; LANL supplied material; no experiments needed, using vendor supplied data.

✓ Vacuum maintenance prescription;

generic description presented in Adv. Cryo. Eng. Vol 49, 2004.





FY 2004 Performance - 2

	Rotating heat pipe assessment;
√	Assessment and thermal model completed, presented and published 2004 ASME Heat Transfer/Fluids Conference; patent applied for
	heat pipe and rotating apparatus being assembled (increased scope at GE request) not listed last year in Plans
✓	Closed loop, passively pumped cooling assessment; developed thermal model; assessed impact on rotating apparatus configuration; three reports; (increased scope at GE request)
	AC loss/Over-current measurement; sensors installed; coil integrated with cryocooler; repairing sensor connections, LANL has fault-current profile
	Assess 2nd generation HTS conductor impact; lower priority task for GE; LANL obtained spec sheet





FY 2005 Plans

- Specific CRADA deliverables (reports) will be met:
 - Extend CRADA with GE to cover new scope.
 - Outgassing material characterization bake-out, emissivity coordination, new samples; submit reports as needed.
 - Rotating heat pipe experiment apparatus assembled, data acquired, compare to model, write report.
 - Closed loop, passively pumped cooling experiment modify rotating apparatus; fabricate/integrate loop; take measurements, compare to model, write report
 - AC loss/Over-current repair sensor connections, take measurements, compare to model predictions, write report
 - 2nd generation HTS conductor impact assess impact, write report.





Research Integration

- Frequent interactions with GE, review direction, efforts, and results
- Exchange of samples, materials, sensors, software models with GE
- Interactions with LANL experts; materials, data acquisition
- Discussions with ORNL correlating emissivity with condensates of residual gases
- Paper on outgassing presented at CEC, published in Advances in Cryogenic Engineering; paper on rotating heat pipe presented at 2004 ASME Heat Transfer/Fluids Engineering Summer Conference, published in proceedings of same; patent applied for
- Interactions with Prof. Razani of University of New Mexico on heat pipes (PhD thesis advisor of LANL student Todd Jankowski)





Summary

- Long Term Vacuum Maintenance:
 - completed getter material and long term maintenance prescription
 - measuring outgassing properties as needed
- Rotating Heat Pipe and Closed-Loop Passively Pumped Cooling
 - assessments and modeling completed
 - apparatus being assembled
- AC Loss/Over-current Experiment
 - apparatus ready, sensor communications in repair
- Need to Extend CRADA to account for increased scope



